



● **Recommended maximum platform size:**

400mmx600mm



**STANDARD CAPACITY :**

60 , 100 , 150 , 250 , 300 , 500, 635 kg

**WIRING:**

RED +INPUT GREEN +OUTPUT  
 BLACK -INPUT WHITE -OUTPUT  
 4 COLOR SHIELD CABLE 9FT(2.7m)

● **Specifications**

Rated output	2.0mV/V ± 10%
Accuracy class	0.03 C3
Non-linearity	0.03% F·S
Hysteresis	0.03% F·S
Non-repeatability	0.02% F·S
Creep in 30 minutes	0.03% F·S
Temperature effect span	15 PPM /°C of Applied Load
Temperature effect zero	26 PPM /°C of Applied Load
Compensated temperature range	-10°C~40°C
Operating temperature range	-40°C~65°C
Zero balance	± 1% F·S
Input resistance	400 ± 15Ω
Output resistance	350 ± 3Ω
Safe overload	150%F·S
Ultimate overload	300%F·S
Excitation voltage	10VAC/DC
Maximum excitation voltage	15VAC/DC
Insulation resistance	≥5000MΩ(50V DC)
Environmental protection	IP67
Material	Aluminum

※All specifications are a maximum as a%( ± ) of full load, otherwise stated.

